

QUICK COUPLINGS PLASTIC

PLUS

**FAST AND RELIABLE PUSH TO CONNECT
MECHANISM**

**A VARIETY OF PLUGS CAN BE
CONNECTED AND USED**

**LIGHTWEIGHT AND ROBUST THANK
TO THE CONSTRUCTION MATERIALS**

**CAN BE USED TO HYDRAULIC OR
PNEUMATICS APPLICATIONS**





p. 395 / **8001**



p. 395 / **8006**



p. 396 / **8007**



p. 396 / **8008**





+4°C ÷ 90°C



Up to 14 Bar at 20°C



Compressed air, water and food fluids suitable with construction materials



Taper gas BSPT ISO 7 - R1/4"



Body: Nylon

Seal: NBR

Internal parts: Acetal resin

Spring: Stainless steel AISI 316

CONNECTION: Acetal resin

PRECAUTIONS

The products are made in plastic and it's necessary to use teflon coating over the thread for installation in order and to prevent air leakage. Be sure to prevent excessive torque when screwing the fittings. Available on demand with EPDM seal




Products in compliance with the directive 2002/95/EC



Products in compliance with the directive 2011/65/EU

8001


Plastic female quick coupler



CODE	T	I	L	H	GR.
8001TR14	R1/4"	10,0	43,0	19	14,2

8006

Plastic male connection




CODE	T	I	L	C	H	GR
8006TR14	R1/4"	10,0	30,0	14,0	17	3,9



8007


Plastic female connection



CODE	T	I	L	C	H	GR.
8007TR14	R1/4"	10,0	28,0	14,0	17	3,6

8008

Plastic barb connection



CODE	ØD	I	L	C	ØH	GR.
8008TR5	5	22,0	39,0	14,0	16,7	2,1
8008TR6	6	24,0	41,0	14,0	16,7	2,35
8008TR8	8	26,0	43,0	14,0	16,8	3,25
8008TR10	10	26,0	43,0	14,0	16,8	3,85
8008TR12	12	28,0	45,0	14,0	16,8	4,15

